

MASTERSOLID



RESILIENT TIRES



The Mastersolid tire is developed with the very latest industrial technology. Quality and state-of-the-art technology guarantees a top-notch product with economical benefit

- **increased shock absorption**
- **extra long wear qualities**
- **exceptional low rolling resistance**

- NATURAL RUBBER
- GOOD RESISTANCE TO FATIGUE
- HIGH STABILITY MAXIMUM SAFETY
- OPTIMAL GRIP AND TRACTION
- NON MARKING COMPOUND IS ALSO AVAILABLE



MASTERSOLID

- TRELLEBORG ENGINEERED
- PREMIUM COMPOUNDS
- HIGH RELIABILITY
- FOR USE IN INDUSTRIAL APPLICATIONS
- AVAILABLE IN POPULAR SIZES



MASTERSOLID

Size	Rim Width	Profile	Plus	Dimensions		Load capacity (kg)				
				max. width	O.D.	Counterbalanced lift trucks up to 25 km/h		Other vehicles		
						Load Wheel	Steering Wheel	6 km/h	10 km/h	25 km/h
mm	mm									
3.00- 4	20.1 C- 4	sl		87	250	260	195	260	235	195
4.00- 8	3.00D- 8	sl	√	130	406	950	730	950	860	730
4.00- 8	3.00D- 8	wing		130	406	950	730	950	860	730
5.00- 8	3.00D- 8	sl	√	143	458	1415	1090	1415	1285	1090
15 x 4 1/2- 8	3.00D- 8	sl	√	132	377	1040	800	1040	940	800
16 x 6- 8	4.33R- 8	sl	√	164	417	1455	1120	1455	1320	1120
18 x 7- 8	4.33R- 8	sl	√	187	453	2145	1650	2145	1950	1650
140/55- 9	4.00E- 9	sl	√	131	377	1170	900	1170	1060	900
6.00- 9	4.00E- 9	sl	√	173	529	1885	1450	1885	1710	1450
21 x 8- 9	6.00E- 9	sl	√	216	524	2755	2120	2755	2505	2120
6.50- 10	5.00F- 10	sl	√	191	576	2340	1800	2340	2185	1800
200/ 50- 10	6.50F- 10	sl	**	221	458	2470	1900	2470	2240	1900
23 x 9- 10	6.50F- 10	sl	√	243	583	3445	2650	3445	3125	2650
7.00- 12	5.00S- 12	sl	√	207	657	2920	2240	2920	2640	2240
23 x 10- 12	8.00G- 12	sl	√	275	583	3770	2900	3770	3420	2900
27 x 10- 12	8.00G- 12	sl	√	275	676	3900	3000	3900	3540	3000
250- 15	7.0- 15	sl	√	265	720	4640	3570	4640	4200	3570
250- 15	7.5- 15	sl		265	720	4640	3570	4640	4200	3570
300- 15	8.0- 15	sl	√	324	823	5850	4500	5850	5310	4500
7.00- 15	5.5- 15	sl	√	213	731	3545	2725	3545	3215	2725
7.50- 15	6.5- 15	sl		234	757	3900	3000	3900	3540	3000
28 x 9- 15	7.0- 15	sl	√	233	693	3900	3000	3900	3540	3000
8.25- 15	6.5- 15	sl	√	253	819	4750	3650	4750	4300	3650
10.00- 20	7.0- 20	sl,fl		292	1029	6000	5000	6000	5455	5000
10.00- 20	7.5- 20	sl,fl		297	1029	6000	5000	6000	5455	5000
10.00- 20	8.0- 20	sl		302	1029	6000	5000	6000	5455	5000
465/ 55- 20	16.0- 20	sl		465	1029	10800	9000	10800	9810	9000

The above load capacities are based on available E.T.R.T.O. specifications for load and steering wheels on counterbalanced forklift trucks.

** Only available in Plus